



PRODUCT NAME	PART NUMBER	COLOR	A	B	C	D	E	F	G	BUNDLE DIAMETER		BREAKING STRENGTH
										MIN.	MAX.	
			in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	lbs (N)
High-Purity Ties	NPC204N	Natural	4.0 (102)	0.179 (4.5)	0.285 (7.25)	0.22 (5.6)	0.25 (6.4)	0.182 (4.6)	0.059 (1.5)	0.13 (3.3)	1.0 (25)	48 (214)
High-Purity Ties	NPC204N	Natural	8.0 (203)	0.179 (4.5)	0.285 (7.25)	0.22 (5.6)	0.25 (6.4)	0.182 (4.6)	0.059 (1.5)	0.13 (3.3)	2.0 (51)	48 (214)
Industrial Ties	NPCi204N	Natural	4.0 (102)	0.179 (4.5)	0.285 (7.25)	0.22 (5.6)	0.25 (6.4)	0.182 (4.6)	0.059 (1.5)	0.13 (3.3)	1.0 (25)	48 (214)
Industrial Ties	NPCi208N	Natural	8.0 (203)	0.179 (4.5)	0.285 (7.25)	0.22 (5.6)	0.25 (6.4)	0.182 (4.6)	0.059 (1.5)	0.13 (3.3)	2.0 (51)	48 (214)
Sterix Ties	NPCS204W	White	4.0 (102)	0.179 (4.5)	0.285 (7.25)	0.22 (5.6)	0.25 (6.4)	0.182 (4.6)	0.059 (1.5)	0.13 (3.3)	1.0 (25)	40 (178)
Sterix Ties	NPCS204W	White	8.0 (203)	0.179 (4.5)	0.285 (7.25)	0.22 (5.6)	0.25 (6.4)	0.182 (4.6)	0.059 (1.5)	0.13 (3.3)	2.0 (51)	40 (178)

MODEL NAME				STRONG-TY™ CABLE TIE SPECS				NOTE(S):							
DESIGNED	HF	15 SEPT 16	MATERIAL	Kynar® PVDF	- USP CLASS VI CERTIFIED MATERIAL				- MANUFACTURED ACCORDING TO ISO 13485 PROCEDURES						
DRAWN	RMG	17 APR 17	QUANTITY	-	- MANUFACTURED AND PACKAGED IN A CLEAN ROOM ENVIRONMENT				- Kynar® IS A REGISTERED TRADEMARK OF ARKEMA, INC.						
CHECKED	HF		SCALE	1.5:1	REV	△	Initial release.								
APPROVED	HF		PROJECTION	⊕	△										
CLIENT:	Nile Polymers www.nilepolymers.com			CREATED BY:	SMARTTCADD www.smarttcadd.com			△							
SHEET				A4				PAGE				1 of 1			