



PRODUCT NAME	PART NUMBER	COLOR	A	B	C	D	E	F	G	BUNDLE DIAMETER		BREAKING STRENGTH
			in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	MIN.	
High-Purity Ties	NPC204N	Natural	4.0 (102)	0.18 (4.5)	0.28 (7.2)	0.22 (5.6)	0.25 (6.4)	0.18 (4.6)	0.06 (1.5)	0.13 (3.3)	1.0 (25)	48 (214)
High-Purity Flex Ties	NPC204NS	Natural	4.0 (102)	0.12 (3.1)	0.19 (4.8)	0.24 (6.1)	0.25 (6.4)	0.16 (4.1)	0.04 (1.0)	0.13 (3.3)	1.0 (25)	18 (80)
High-Purity Ties	NPC208N	Natural	8.0 (203)	0.18 (4.5)	0.28 (7.2)	0.22 (5.6)	0.25 (6.4)	0.18 (4.6)	0.06 (1.5)	0.13 (3.3)	2.0 (51)	48 (214)

MODEL NAME					STRONG-TY® CABLE TIE SPECS					NOTE(S):		
DESIGNED	HF	15 SEPT 16	MATERIAL	Kynar® PVDF	- USP CLASS VI CERTIFIED MATERIAL - MANUFACTURED ACCORDING TO ISO 13485 PROCEDURES - MANUFACTURED AND PACKAGED IN A CLEAN ROOM ENVIRONMENT - Kynar® IS A REGISTERED TRADEMARK OF ARKEMA, INC.							
DRAWN	RMG	17 APR 17	QUANTITY	-								
CHECKED	HF		SCALE	1.5:1	REV	△	Version 1.1					
APPROVED	HF		PROJECTION	⊕	△							
CLIENT:	Nile Polymers www.nilepolymers.com		CREATED BY:	SMARTTCADD www.smarttcadd.com	△							
					SHEET	A4	PAGE	1 of 1				